



Site Search:
[advanced](#)



[BUY PUBLICATIONS](#)
[A-Z RESOURCE LIST](#)
[FIND A FEDERAL DEPOSITORY LIBRARY](#)

[Home Page](#) > [Executive Branch](#) > [Code of Federal Regulations](#) > [Electronic Code of Federal Regulations](#)



e-CFR Data is current as of January 20, 2012

Title 40: Protection of Environment

[Browse Previous](#) | [Browse Next](#)

PART 450 CONSTRUCTION AND DEVELOPMENT POINT SOURCE CATEGORY

Section Contents

[Subpart A General Provisions](#)

[§ 450.10 Applicability.](#)

[§ 450.11 General definitions.](#)

[Subpart B Construction and Development Effluent Guidelines](#)

[§ 450.21 Effluent limitations reflecting the best practicable technology currently available \(BPT\).](#)

[§ 450.22 Effluent limitations reflecting the best available technology economically achievable \(BAT\).](#)

[§ 450.23 Effluent limitations reflecting the best conventional pollutant control technology \(BCT\).](#)

[§ 450.24 New source performance standards reflecting the best available demonstrated control technology \(NSPS\).](#)

Authority: 33 U.S.C. 101, 301, 304, 306, 308, 401, 402, 501 and 510.

Source: 74 FR 63057, Dec. 1, 2009, unless otherwise noted.

Subpart A General Provisions

[↑](#) [top](#)

§ 450.10 Applicability.

[↑](#) [top](#)

DATABASE FEATURES

- [Browse](#)
- [Simple Search](#)
- [Advanced Search](#)
- * [Boolean](#)
- * [Proximity](#)
- [Search History](#)
- [Search Tips](#)
- [Corrections](#)
- [Latest Updates](#)
- [User Info](#)
- [FAQs](#)
- [Agency List](#)
- [Incorporation by Reference](#)
- [e-CFR Main Page](#)

RELATED RESOURCES

- [Code of Federal Regulations](#)
- [Federal Register](#)
- [List of CFR Sections Affected](#)
- [Regulations.gov](#)
- [Unified Agenda](#)
- [All NARA Publications](#)

ABOUT GOVERNMENT



[Ben's Guide to U.S. Government](#)



(a) This part applies to discharges associated with construction activity required to obtain NPDES permit coverage pursuant to 40 CFR 122.26(b)(14)(x) and (b)(15).

(b) The provisions of §450.22(a) do not apply to discharges associated with interstate natural gas pipeline construction activity.

(c) The New Source Performance Standards at §450.24 apply to all new sources and are effective February 1, 2010.

(d) The BPT, BCT and BAT effluent limitations at §450.21 through 450.23 apply to all sources not otherwise covered by paragraph (c) of this section and are effective February 1, 2010.

§ 450.11 General definitions.



(a) *New source.* New source means any source, whose discharges are defined in 40 CFR 122.26(b)(14)(x) and (b)(15), that commences construction activity after the effective date of this rule.

(b) [Reserved]

Subpart B Construction and Development Effluent Guidelines



§ 450.21 Effluent limitations reflecting the best practicable technology currently available (BPT).



Except as provided in 40 CFR 125.30 through 125.32, any point source subject to this subpart must achieve, at a minimum, the following effluent limitations representing the degree of effluent reduction attainable by application of the best practicable control technology currently available (BPT).

(a) *Erosion and sediment controls.* Design, install and maintain effective erosion controls and sediment controls to minimize the discharge of pollutants. At a minimum, such controls must be designed, installed and maintained to:

- (1) Control stormwater volume and velocity within the site to minimize soil erosion;
- (2) Control stormwater discharges, including both peak flowrates and total stormwater volume, to minimize erosion at outlets and to minimize downstream channel and streambank erosion;
- (3) Minimize the amount of soil exposed during construction activity;
- (4) Minimize the disturbance of steep slopes;
- (5) *Minimize sediment discharges from the site.* The design, installation and maintenance of erosion and sediment controls must address factors such as the amount, frequency, intensity and duration of precipitation, the nature of resulting stormwater runoff, and soil characteristics, including the range of soil particle sizes expected to be present on the site;
- (6) Provide and maintain natural buffers around surface waters, direct stormwater to vegetated areas to increase sediment removal and maximize stormwater infiltration, unless infeasible; and
- (7) Minimize soil compaction and, unless infeasible, preserve topsoil.

(b) *Soil stabilization.* Stabilization of disturbed areas must, at a minimum, be initiated immediately whenever any clearing, grading, excavating or other earth disturbing activities have permanently ceased on any portion of the site, or temporarily ceased on any portion of the site and will not resume for a period exceeding 14 calendar days. Stabilization must be completed within a period of time determined by the permitting authority. In arid, semiarid, and drought-stricken areas where initiating vegetative stabilization measures immediately is infeasible, alternative stabilization measures must be employed as specified by the permitting authority.

(c) *Dewatering.* Discharges from dewatering activities, including discharges from dewatering of trenches and excavations, are prohibited unless managed by appropriate controls.

(d) *Pollution prevention measures.* Design, install, implement, and maintain effective pollution prevention measures to minimize the discharge of pollutants. At a minimum, such measures must be designed, installed, implemented and maintained to:

(1) Minimize the discharge of pollutants from equipment and vehicle washing, wheel wash water, and other wash waters. Wash waters must be treated in a sediment basin or alternative control that provides equivalent or better treatment prior to discharge;

(2) Minimize the exposure of building materials, building products, construction wastes, trash, landscape materials, fertilizers, pesticides, herbicides, detergents, sanitary waste and other materials present on the site to precipitation and to stormwater; and

(3) Minimize the discharge of pollutants from spills and leaks and implement chemical spill and leak prevention and response procedures.

(e) *Prohibited discharges.* The following discharges are prohibited:

Pollutant	Daily maximum value (NTU) ¹
Turbidity	280

¹Nephelometric turbidity units.

(2) Conduct monitoring consistent with requirements established by the permitting authority. Each sample must be analyzed for turbidity in accordance with methods specified by the permitting authority.

(b) If stormwater discharges in any day occur as a result of a storm event in that same day that is larger than the local 2-year, 24-hour storm, the effluent limitation in paragraph (a)(1) of this section does not apply for that day.

(c) *Erosion and sediment controls*. The limitations are described at §450.21(a).

(d) *Soil stabilization*. The limitations are described at §450.21(b).

(e) *Dewatering*. The limitations are described at §450.21(c).

(f) *Pollution prevention measures*. The limitations are described at §450.21(d).

(g) *Prohibited discharges*. The limitations are described at §450.21(e).

(h) *Surface outlets*. The limitations are described at §450.21(f).

[74 FR 63057, Dec. 1, 2009, as amended at 75 FR 10439, Mar. 8, 2010]

Effective Date Note: At 75 FR 68217, Nov. 5, 2010, in §450.22, paragraphs (a) and (b) were stayed indefinitely, effective Jan. 4, 2011.

§ 450.23 Effluent limitations reflecting the best conventional pollutant control technology (BCT).



Except as provided in 40 CFR 125.30 through 125.32, any point source subject to this subpart must achieve, at a minimum, the following effluent limitations representing the degree of effluent reduction attainable by application of the best conventional pollutant control technology (BCT). The effluent limitations are described at §450.21.

§ 450.24 New source performance standards reflecting the best available demonstrated control technology (NSPS).



Any new source subject to this subpart must achieve, at a minimum, the following new source performance standards representing the degree of effluent reduction attainable by application of the best available demonstrated control technology (NSPS): The standards are described at §450.22.

[Browse Previous](#) | [Browse Next](#)

For questions or comments regarding e-CFR editorial content, features, or design, email ecfr@nara.gov.

For questions concerning e-CFR programming and delivery issues, email webteam@gpo.gov.

[Section 508 / Accessibility](#)